



Polyurethane 2k Sealer

Description

2K Polyurethane sanding sealer contains high quality acrylic resin & filler. It is used as under coat for bare and unfinished wood that need high filling power. It is specialized for interior and exterior wood surfaces.

Advantages

High filling power – hardness – fast drying – easy sanding – self insulator against wood secretes - high weather resistance - .

Application Method

Surface must be clean, dry and free of dust, grease or oils.

Sand the surface well using sandpaper no. 320, then dilutes to reach spray viscosity.

Mixing ratio:

Polyurethane Sealer	Hardener	Polyurethane thinner
100	50	25

Apply using spray gun nozzle: 1.5 – 1.8 mm

Apply two coats with flash off - 5 minutes.

Sand using sandpaper no. 320 for smooth surface.

Drying Time

Drying Time	Surface Dry	Complete Dry
At Temperature 25c ^o	2 hrs.	4 hrs.

This information is given to the best of our knowledge. Because of the multitude of formulation, production, and application conditions, all the above-mentioned statements have to be adjusted to the circumstances of the processor. No liabilities, including those for patent rights, can be derived from this fact for individual cases.

Violette for chemical industries.
Tel: (+2) 03 46 222 30, Fax: (+2) 03 46 222 40



Coverage Rate

(6 – 8) m²/kg

Shelf Life

Two years from production date if stored in original package at 25C⁰.

Precautions

Keep out of reach of children. Don't use the empty can in food uses.

This information is given to the best of our knowledge. Because of the multitude of formulation, production, and application conditions, all the above-mentioned statements have to be adjusted to the circumstances of the processor. No liabilities, including those for patent rights, can be derived from this fact for individual cases.

Violette for chemical industries.
Tel: (+2) 03 46 222 30, Fax: (+2) 03 46 222 40