



Wood Stain

Description

Alcohol based wood stain, enriches the appearance of unfinished wood, as it provides ultimate color and beauty to your wood. It can be used for bare and unfinished wood including floors, doors, wood, work, furniture and cabinets.

Application Method

Surface must be clean, dry and free of dust, grease or oils.

Remove all dust by vacuuming or wiping with a damp cloth.

Mixing ratio:

Wood Stain	Thinner or Alcohol
100	10-25

Apply using spray gun nozzle: 1 – 4 mm or via sponge.

Apply till obtain desired color depth.

Drying Time

Drying Time	Complete Dry
At Temperature 25c°	3-6 min

Finish recommendation:

It can be coated with all types of sealers like N.C, polyurethane and polyester sealer. Also it can be top coated with all general finishes top coats like lacquers and varnishes.

This information is given to the best of our knowledge. Because of the multitude of formulation, production, and application conditions, all the above-mentioned statements have to be adjusted to the circumstances of the processor. No liabilities, including those for patent rights, can be derived from this fact for individual cases.

Violette for chemical industries.
Tel: (+2) 03 46 222 30, Fax: (+2) 03 46 222 40



Coverage Rate

(10 – 12) m²/kg

Shelf Life

Two years from production date if stored in original package at 25C⁰.

Container:

Available in: 125ml – 250ml – 1000ml.

Precautions

Keep out of reach of children. Don't use the empty can in food uses.

This information is given to the best of our knowledge. Because of the multitude of formulation, production, and application conditions, all the above-mentioned statements have to be adjusted to the circumstances of the processor. No liabilities, including those for patent rights, can be derived from this fact for individual cases.

Violette for chemical industries.
Tel: (+2) 03 46 222 30, Fax: (+2) 03 46 222 40