



2k Glossy Clear Coat

Description

2K Polyurethane glossy varnish contains the best level of acrylic resin & special additives to give high gloss and hardness. It is specialized interior and exterior wood finishes.

Advantages

High gloss and gloss retention – high abrasion resistance – high weather resistance – high yellowish resistance – chemical and mechanical resistance - fast drying.

Application Method

Surface should be clean and free of dust grease and oil.

New wood surfaces must be sealed first by using grit sandpaper number 320 to obtain a smooth surface.

Old varnish surfaces must be sanded using grit sand paper number 1000 before applying polyurethane varnish.

Mixing ratio:

Polyurethane Varnish	Hardener	Polyurethane thinner
100	50	15

Apply using spray gun nozzle: 1.5 – 1.8 mm.

Apply two coats with flash off - 5 minutes.

Drying Time

Drying Time	Surface Dry	Complete Dry
At Temperature 25c°	2 hrs.	8 hrs.

This information is given to the best of our knowledge. Because of the multitude of formulation, production, and application conditions, all the above-mentioned statements have to be adjusted to the circumstances of the processor. No liabilities, including those for patent rights, can be derived from this fact for individual cases.

Violette for chemical industries.
Tel: (+2) 03 46 222 30, Fax: (+2) 03 46 222 40

www.violettecoatings.com



Coverage Rate

(6 – 8) m²/kg

Shelf Life

Two years from production date if stored in original package at 25C°.

Precautions

Keep out of reach of children. Don't use the empty can in food uses.

This information is given to the best of our knowledge. Because of the multitude of formulation, production, and application conditions, all the above-mentioned statements have to be adjusted to the circumstances of the processor. No liabilities, including those for patent rights, can be derived from this fact for individual cases.

Violette for chemical industries.
Tel: (+2) 03 46 222 30, Fax: (+2) 03 46 222 40

www.violettecoatings.com